6590 Top Gun St. San Diego, CA 92121 www.philihardware.com Tel: 858-642-0450 Fax: 858-642-0454

V052623

Advantage Exit Device ETL7 Series Escutcheon Lever Trim

Features


- Designed to Use with Grade 1 Exit Device
- Clutch Function Standard
- Standard For 1-3/4" Door Thickness
- Optional For 2" ~ 2-1/4" Door Thickness



Specifications

Certification	California State Reference Code: (Formerly Title 19, California State Fire Marshall Standard) For Levers with Returns to Within 1/2" of Door Face.	
Exposed Trim	Wrought Zinc with Steel Construction, Pressure Cast Zinc Lever	
Keys	2 Keys Per Set. Keying As Requested (KA, KD, MCK, MK, GMK)	
Mortise Cylinder	SCC Standard Optional with SFIC, LFIC, KW1	
Lever Style	CT (Charlotte), SD (San Diego)	
Finishes (BHMA)	US26D (626), US19 (622), ALUM, DURO	

Dimensions



Functions

ETL700 – Entry
ETL704 – Storeroom
ETL701 – Passage
ETL715 – Dummy
ETL700ICB – SFIC Entry*
ETL704ICB – SFIC Storeroom*
ETL700ICS – LFIC Entry**
ETL704ICS – LFIC Storeroom**
*SFIC (Less Core)
** LFIC (Less Core)

SAN DIEGO · CHICAGO · ATLANTA · DALLAS